

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

[Back to list](#)

JP 08-029757

1-1/1

[Next page](#)

From 1

- 1

Count

Display format: ----- Select the type of output. -----


[Display checked documents](#)
[Check All](#)
[Uncheck All](#)


** Result [P] ** Format(P801) 2004.03.15 1/ 1

Application no/date: 1981- 74735 [1981/ 5/18]

Date of request for examination: [1983/12/22]

Accelerated examination ()

Public disclosure no/date: 1982-188297  Translate [1982/11/19]Examined publication no/date (old law): 1986- 29757  Translate [1986/ 7/ 9]

Registration no/date: 1363055 [1987/ 2/ 9]

Examined publication date (present law): [1987/ 6/18]

PCT application no:

PCT publication no/date:

Applicant: SANYO ELECTRIC CO LTD

Inventor: RIKI TAKAMI, HATSUDA KOICHI

IPC: D06F 43/06

FI: D06F 43/06 C

F-Term: 3B155AA24, BA01, BB01, BB02, BB05, CB41, CB49, CE55, CC09, CC12, CC13, FE02, GA09, MA01, MA02

Expanded classification: 281, 304

Fixed keyword:

Citation: [, , , ,] (, , ,)

Title of invention: DRY CLEANING APPARATUS

Abstract: It is integrated with medium light filter and botantoratsupu and lint light filter, simplification of assembling of apparatus and operation is measured, and maintenance service of apparatus facilitates cleaning of light filter member of framework particularly.

The first cleaning solvent in base tank 1 is led in watsushiya 7 through 2, 3, the sixth solenoid valve pump solenoid valve 41 and the third solenoid valve 6.

And, in cleaning aftertreatment, *nari put returning medium circuit in watsushiya 7 from drain cable duct 25 of watsushiya 7, and cleaning solvent is circulated forcibly, as for light filter 27, ho* does all insoluble material which left hisenbutsu.

In other words,

Light filter 27 plays a role as medium light filter and botantoratsupu. When cleaning treatment is over, it makes the purification medium which did giketsu to guidance, distillation capacitor 12 to distiller 11 in cleaning solvent in watsushiya 7 return through mist separator 13 to base tank 1.

In dry aftertreatment, 27 light filter niyotsure ho* can place the waste thread which is contaminated within a dry wind.

